

LUMINARY
100-014, Blue Mist

TECHNICAL INFORMATION

CATEGORY: Panel
CONTENT: 63% Recycled Polyester (60% Pre-/3% Post-Consumer),
37% Polypropylene
BACKING: None
FINISH: Polyester Binder
WIDTH: 66"
WEIGHT: 10.6 oz./ln yd
SHOWN RAILROADED: No
DIRECTIONAL: Yes
APPROX. ROLL SIZE: 57 yards


PERFORMANCE



ABRASION RESISTANCE: n/a
BREAKING STRENGTH: Warp 175.0 / Fill 125.0
COLORFASTNESS TO CROCKING: Dry: Class 4 min/Wet: Class 3 min
COLORFASTNESS TO LIGHT: 60 hours
PILLING RESISTANCE: Class N/A

FLAMMABILITY

PASSES AB 2998 COMPLIANT
ASTM E84 CLASS 1 OR A (UNADHERED)



REDUCED ENVIRONMENTAL IMPACT

GREENGUARD GOLD CERTIFIED
PFAS FREE
NO FR ADDITIVES
HHI / GREENHEALTH COMPLIANT
NO ANTIMICROBIAL ADDITIVES
NO ANTIBACTERIAL ADDITIVES
MINDFUL MATERIALS COMPLIANT
BPA FREE
FORMALDEHYDE FREE
TRIS FREE
PROP 65 COMPLIANT
MILLED IN AMERICA
REACH COMPLIANT
ROHS COMPLIANT
DOES NOT CONTAIN CONFLICT MINERALS

WARRANTY

PANEL | '5' FIVE YEAR WARRANTY

See [Warranty Terms](#) for more information.

DYE TRANSFER DISCLAIMER

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colors. This phenomenon is increased by humidity and temperature and is irreversible. Mayer Fabrics will not assume responsibility for dye transfer caused by external contaminants. Please check compatibility when using this product in combination with painted or varnished surfaces.

ADDITIONAL INFORMATION

Custom Colors: All patterns can be custom colored. Minimum yardage applies.

Digital Swatch Color Matching: Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation.

CLEANING & MAINTENANCE

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.



® This 100% polyester fabric is included in the Underwriter's Laboratory Fabric Recognition Program. Additional testing of this U.L. recognized component is not required on approved panels from participating manufacturers.