

VENUE

359-007, Shiitake

TECHNICAL INFORMATION

CATEGORY: Upholstery, Panel
 CONTENT: 100% Recycled Polyester (60% Pre-/40% Post-Consumer)/60% Recycled Polyester/40% Recycled Polyester
 BACKING: Eco Polyester
 FINISH: None
 WIDTH: 54
 WEIGHT: 7.8 oz./In yd
 VISUAL REPEAT: 1.2 in/3.05 cm H, 1.75 in/4.44 cm V
 SHOWN RAILROADED: No
 DIRECTIONAL: Yes
 APPROX. ROLL SIZE: 60 yards



PERFORMANCE



ABRASION RESISTANCE: Passes 60,000 Double Rubs (Wyzenbeek/Cotton Duck)
 BREAKING STRENGTH: Warp 159.0 / Fill 115.0
 COLORFASTNESS TO CROCKING: Dry: Class 4/Wet: Class 4
 COLORFASTNESS TO LIGHT: 40 hours
 PILLING RESISTANCE: Class 4
 SEAM SLIPPAGE: Warp 39.0 / Fill 41.0

REDUCED ENVIRONMENTAL IMPACT

GREENGUARD GOLD CERTIFIED
 HHI / GREENHEALTH COMPLIANT
 DOES NOT CONTAIN CONFLICT MINERALS
 MILLED IN AMERICA

FLAMMABILITY

PASSES NFPA 260/UFAC CLASS 1
 AB 2998 COMPLIANT
 CAL 117 SECTION E

WARRANTY

STANDARD UPHOLSTERY | '5' FIVE YEAR WARRANTY
See [Warranty Terms](#) for more information.

DYE TRANSFER DISCLAIMER

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colors. This phenomenon is increased by humidity and temperature and is irreversible. Mayer Fabrics will not assume responsibility for dye transfer caused by external contaminants. Please check compatibility when using this product in combination with painted or varnished surfaces.

ADDITIONAL INFORMATION

Custom Colors: All patterns can be custom colored. Minimum yardage applies.

Digital Swatch Color Matching: Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation.

CLEANING & MAINTENANCE

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.



® This 100% polyester fabric is included in the Underwriter's Laboratory Fabric Recognition Program. Additional testing of this U.L. recognized component is not required on approved panels from participating manufacturers.