SPECIFICATIONS - VIBRANT (833)

VIBRANT

833-017, Alabaster

TECHNICAL INFORMATION

CATEGORY: Upholstery CONTENT: 66% Recycled Polyester (38% Pre-/28% Post-Consumer)/34% Cotton BACKING: None FINISH: None WIDTH: 54" WEIGHT: 14.72 oz./ln yd VISUAL REPEAT: 1.25 in/3.18 cm H, 1.0 in/2.54 cm V SHOWN RAILROADED: No DIRECTIONAL: Yes APPROX. ROLL SIZE: 55 yards

ABRASION RESISTANCE: Passes 51,000 Double Rubs (Wyzenbeek/Cotton Duck) BREAKING STRENGTH: Warp 215.0 / Fill 138.0 COLORFASTNESS TO CROCKING: Dry: Class 4 min/Wet: Class 3 min COLORFASTNESS TO LIGHT: 40 hours PILLING RESISTANCE: Class 5 SEAM SLIPPAGE: Warp 52.0 / Fill 60.0

REDUCED ENVIRONMENTAL IMPACT GREENGUARD GOLD CERTIFIED HHI / GREENHEALTH COMPLIANT MILLED IN AMERICA DOES NOT CONTAIN CONFLICT MINERALS

FLAMMABILITY

PASSES NFPA 260/UFAC CLASS 1 AB 2998 COMPLIANT CAL 117 SECTION E MAY COMPLY WITH CAL. TECH. BUL. 133 WHEN COMBINED WITH APPROPRIATE COMPONENTS.

© Mayer Fabrics 2011 Specifications are subject to change.

MAYERFABRICS

WARRANTY

STANDARD UPHOLSTERY | '5' FIVE YEAR WARRANTY See <u>Warranty Terms</u> for more information.

DYE TRANSFER DISCLAIMER

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colors. This phenomenon is increased by humidity and temperature and is irreversible. Mayer Fabrics will not assume responsibility for dye transfer caused by external contaminants. Please check compatibility when using this product in combination with painted or varnished surfaces.

ADDITIONAL INFORMATION

Custom Colors: All patterns can be custom colored. Minimum yardage applies.

Digital Swatch Color Matching: Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation.

CLEANING & MAINTENANCE

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding.