# SPECIFICATIONS - DANDE (DAN)

## DANDE

DN-007, Ecru

### **TECHNICAL INFORMATION**

CATEGORY: Upholstery CONTENT: 80% Vinyl - Phthalate Free face, 20% Polyester backing BACKING: 100% Brushed Polyester Knit FINISH: Soil & Stain Resistant Top Coat with Ink Resistant Technology WIDTH: 54" WEIGHT: 30 oz./In yd VISUAL REPEAT: 20.125 in/51.12 cm H, 20.125 in/51.12 cm V SHOWN RAILROADED: No DIRECTIONAL: Yes APPROX. ROLL SIZE: 30 yards APPLICATION: Indoor / Atrium

### 

ABRASION RESISTANCE: Passes 350,000 Double Rubs\* (Wyzenbeek/Cotton Duck) BREAKING STRENGTH: Warp 98.0 / Fill 83.0 COLORFASTNESS TO CROCKING: Dry: Class 4 min/Wet: Class 4 min COLORFASTNESS TO LIGHT: 650 hours PILLING RESISTANCE: Class n/a SEAM STRENGTH: Warp 55.0 / Fill 39.0 INK RESISTANT LIQUID BARRIER DENIM DYE RESISTANT

\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

### FLAMMABILITY

PASSES CAL TB 117-2013 NFPA 260/UFAC CLASS 1 AB 2998 COMPLIANT FMVSS 302

# MAYERFABRICS



**REDUCED ENVIRONMENTAL IMPACT GREENGUARD GOLD CERTIFIED** PHTHALATE FREE PFAS FREE NO FR ADDITIVES NO ANTIMICROBIAL ADDITIVES NO ANTIBACTERIAL ADDITIVES **BPA FREE** FORMALDEHYDE FREE VEGAN COMPLIANT TRIS FREE HPD AVAILABLE **PROP 65 COMPLIANT REACH COMPLIANT ROHS COMPLIANT** DOES NOT CONTAIN CONFLICT MINERALS CFFA HEALTHCARE 201 COMPLIANT

### WARRANTY

STANDARD UPHOLSTERY | '5' FIVE YEAR WARRANTY See <u>Warranty Terms</u> for more information.

### DYE TRANSFER DISCLAIMER

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colors. This phenomenon is increased by humidity and temperature and is irreversible. Mayer Fabrics will not assume responsibility for dye transfer caused by external contaminants. Please check compatibility when using this product in combination with painted or varnished surfaces.

### ADDITIONAL INFORMATION

Custom Colors: All patterns can be custom colored. Minimum yardage applies.

Digital Swatch Color Matching: Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation.

### **CLEANING & MAINTENANCE**

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

CFC: Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below. Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry.

Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry.

Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.