



Application
Seating


Content
82% Polyester, 18% Cotton

Width
54 inches

Abrasion
Exceeds 100,000 Double Rubs

Finish
Stain Repellent


Reduced Environmental Impact
GREENGUARD Gold Certified



620-002
Sunglow



620-013
Limonade



620-063
Chino




620-040
Praline




620-009
Bittersweet




620-003
Forest




620-023
Fern




620-019
Amber



620-073
Celery



620-033
Everglade




620-027
Ivory




620-036
Dove



620-001
Paprika



620-043
Bluegrass



620-053
Oregano




620-007
Ecru



620-030
Bark



620-008
Malbec



620-054
Aegean



620-037
Sand




620-017
Buff




620-026
Cloud




620-011
Wildberry



620-034
Aquamarine



620-047
Almond




620-012
Caramel



620-016
Storm



620-005
Hyacinth



620-024
Cyan




620-050
Mushroom




620-029
Spice



620-006
Charcoal



620-004
Indigo



620-014
Cerulean



620-000
Sable



620-010
Fudge



620-020
Seal

TECHNICAL INFORMATION

Content: 82% Polyester, 18% Cotton Width: 54" Weight: 16.48 oz./linear yd.	Backing: Acrylic Finish: Stain Repellent Cleaning Code: S	Visual Repeat: None Directional: Yes Railroaded: No
--	---	---

PERFORMANCE (*ACT® Registered Certification Marks)	Test Method	Results
Surface Abrasion: Heavy Duty 	ASTM-D-4157	Exceeds 100,000 Double Rubs
Breaking Strength: 	ASTM-D-5034	Warp 187 lbs/Fill 183 lbs
Seam Slippage: 	ASTM-D-4034	Warp 103 lbs/Fill 99 lbs
Pilling Resistance:	ASTM-D-3511	Class 5
Colorfastness to Crocking: 	AATCC-8	Dry: Class 4 min. / Wet: Class 3 min.
Colorfastness to Light: 	AATCC-16	Class 4 min. at 40 hours

FLAMMABILITY

California Technical Bulletin 117, Section E NFPA 260 (Equivalent to UFAC) Class 1	Passes Passes
May comply with California Technical Bulletin 133 when combined with appropriate components.	

REDUCED ENVIRONMENTAL IMPACT

GREENGUARD Gold Certified products are tested for low chemical emissions to standard UL 2818. For more information, visit UL.com/gg.

CLEANING INFORMATION

S: Solvent – Spot clean using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding.

ADDITIONAL INFORMATION

Custom Capabilities: All patterns can be custom colored. Minimum yardage applies.
Memo Samples: Please keep this card intact. Individual memo samples can be ordered on our website or by contacting customer service.
Color Matching: Mayer Fabrics always attempts to ship a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly.
Specifications: Specifications are correct at the time of printing. Current specifications are available on our website.
For information or assistance with products or services, call us at 800.428.4415 or refer to our website, www.mayerfabrics.com.

