




895-009 Tangelo




895-003 Citronella




895-002 Marigold



895-019 Poppy




895-013 Jungle



895-007 Beach




895-001 Ruby




895-023 Turquoise




895-000 Java




895-005 Wildberry




895-014 Capri




895-016 Limestone



895-024 Periwinkle



895-004 Indigo



895-006 Graphite

Application

Multi-Use

Content

100% Trevira CS Inherently  
FR Polyester

Width

54 inches

Abrasion

Exceeds 102,000 Double Rubs

Finish

None

Reduced Environmental Impact

GREENGUARD Gold Certified

## TECHNICAL INFORMATION

Content: 100% Trevira CS Inherently FR Polyester  
Width: 54"  
Weight: 15.86 oz./linear yard

Backing: None  
Finish: None  
Cleaning Code: S

Approx. Repeat: Non-Matching  
Directional: Yes  
Railroaded: No

## PERFORMANCE

## Test Method

## Results

|                              |                           |                                     |
|------------------------------|---------------------------|-------------------------------------|
| Surface Abrasion: Heavy Duty | ASTM-D-3597 (Cotton Duck) | Exceeds 102,000 Double Rubs         |
| Breaking Strength:           | ASTM-D-3597               | Warp 296 lbs / Fill 333 lbs         |
| Seam Slippage:               | ASTM-D-3597               | Warp 121 lbs / Fill 90 lbs          |
| Pilling Resistance:          | ASTM-D-3511               | Class 4                             |
| Colorfastness to Crocking:   | AATCC-8                   | Dry: Class 4 min / Wet: Class 4 min |
| Colorfastness to Light:      | AATCC-16A                 | Class 4.5 at 60 hours               |

Class in the colorfastness requirements is based on a numerical scale of 5 for negligible or no color transfer to 1 for very severe color change or color transfer.

## FLAMMABILITY

California Technical Bulletin 117-2013 Passes  
NFPA 260/UFAC Class 1 Passes  
FAA/FAR 25.853(a) & Appendix F Part I(a)(ii) Passes  
IMO A.652(16) 8.2 & 8.3 Passes  
NFPA 701 Test Method 1 Passes  
Should comply with Cal 133 when combined with appropriate components

## REDUCED ENVIRONMENTAL IMPACT

This product is **GREENGUARD Gold Certified for low chemical and particle emissions to UL standard UL 2818 and may contribute to LEED certification. For complete information visit [mayerfabrics.com](http://mayerfabrics.com) and [UL.com/gg](http://UL.com/gg).**

## CLEANING INFORMATION

S: Solvent – Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

Prompt cleaning is always recommended. For detailed care and cleaning information, please refer to the Mayer Fabrics website or contact customer service.

## ADDITIONAL INFORMATION

**Custom Capabilities:** All patterns can be custom colored. Minimum yardage applies.

**Memo Samples:** Please keep this card intact. Individual memo samples can be ordered on our website or by contacting customer service.

**Fabric Color Matching:** Mayer Fabrics always attempts to ship a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly.

**Digital Swatch Card Color Matching:** Due to color variations on different monitors and color printers, actual swatch colors may vary slightly. Please request a memo sample from Mayer Fabrics to ensure proper color representation.

**Specifications:** Specifications are correct at the time of printing. Current specifications are available on our website.

**For information or assistance with products or services, call us at 800.428.4415 or refer to our website, [www.mayerfabrics.com](http://www.mayerfabrics.com).**



This fabric meets or exceeds  
these ACT performance guidelines.  
\*Certification Marks owned by ACT®

